Autoconer upgrade kit Suction nozzle and Smartjet



Autoconer Upgrade Kit – Suction Nozzle and Smartjet



Your benefits:

- Energy efficiency
- Optimized package quality
- Yarn resources saved
- Operator's workload reduced
- Higher productivity

The Power Combination for Efficient Upper Yarn Pick-Up

Customers can now switch to the fastest and most economical upper yarn pick for their Autoconer. The new suction nozzle catches the upper yarn measurably faster and more reliably. With the optional Smartjet, even the doffer assists. This means avoiding red lights, saving energy and yarn and it doesn't need as many workers.

New suction nozzle

Standard suction nozzles replaced with new, flow- optimized and highly effective suction nozzles

Energy efficiency

• Minimized energy costs thanks to possible vacuum reduction

Optimized package quality

• Improved upper yarn pick-up protects the package surface; particularly recommended in the fine yarn count range

Yarn resources saved

Less yarn waste

Operator's workload reduced

- Fewer red lights
- Increased pick-up rates reduce the manual effort required

Smartjet

The unique Smartjet nozzle retrofitted in the doffer for additional efficiency in upper yarn pick-up

Additional reduction of the operator's workload

- Smartjet supports the suction nozzle with upper yarns that are difficult to pick up
- Fewer red lights
- Effort required for manual upper yarn searching thus additionally reduced by around 50% to 80%

Higher productivity

· Less downtime for the winding unit



High upper yarn pick-up reliability with energy-saving vacuum ensures minimal energy and consumption costs with the new suction nozzle.



The Smartjet power nozzle – in the doffer – increases the success rate of upper yarn searching even further.

Suction nozzle with smart aerodynamics

The latest Autoconer flow technology is easy to recognize by the new rubber lip. Thanks to the aerodynamically optimized inner and outer moulds, the new suction nozzle impresses with extremely efficient air guidance. Customers benefit from maximum upper yarn pick-up reliability with energy-saving vacuum.

Optional additional power: Smartjet in the doffer

With the Smartjet, customers can increase the efficiency of upper yarn searching even further. Before a winding unit activates a red light, it requests the doffer. With its unique Smartjet power nozzle, the doffer increases the success rate, even with upper yarns that are difficult to pick up.

Customer advantages: less downtime, significantly reduced operator workload and greater process reliability.

Particularly clever: Machine retrofit with suction nozzle and Smartjet as an attractive power combination for maximum upper yarn pick-up efficiency.

Autoconer X5 as an example: Up to 1.6% increased production with Smartjet



Autoconer Upgrade Kit

Contents of Upgrade Kit

New suction nozzle	Smartjet
New suction nozzle with rubber lip	• Smartjet
 Including all of the necessary additional components (vary depending on the type of machine) 	Sheet metal parts
Fastening material	• Wiring

Range of application

New suction nozzle	Smartjet
• For all Autoconer 5, X5 machines	 For all Autoconer X5, 6 machines
• For all Autoconer 338 machines	

Service

- Expert installation and start-up by experienced Rieter service technicians
- Quick, professional, simple and reliable processing

Order numbers

Please specify machine number	
New suction nozzle for Autoconer 338	148-400.860
New suction nozzle for Autoconer 5, X5	149-400.121
Smartjet for Autoconer X5	149-400.133
Smartjet for Autoconer 6	159-400.026
Smartjet for Autoconer X6	171-400.049

Rieter Machine Works Ltd. Klosterstrasse 20 CH-8406 Winterthur T +41 52 208 7171 F +41 52 208 8320 machines@rieter.com aftersales@rieter.com

www.rieter.com

Rieter India Private Ltd. Gat No. 768/2, Village Wing Shindewadi-Bhor Road Taluka Khandala, District Satara IN-Maharashtra 412 801 +91 2169 664 141 F +91 2169 664 226

Rieter (China) Textile Instruments Co., Ltd. 390 West Hehai Road Changzhou 213022, Jiangsu P.R. China T +86 519 8511 0675 F +86 519 8511 0673

The data and illustrations in this brochure and on the corresponding data carrier refer to the date of printing. Rieter reserves the right to make any necessary changes at any time and without special notice. Rieter systems and Rieter innovations are protected by patents.

3468-v1 en 2408